



Shell Rimula R6 LM 10W-40

- Low Emissions
- Maintenance Saving

Fully Synthetic Heavy Duty Diesel Engine Oil

Shell Rimula R6 LM oil features “Low-SAPS” additive technology and unique anti-wear system. Protective power is enhanced with synthetic technology, resulting in maintenance saving long drain capability, exceptional wear and cleanliness performance.



Performance, Features & Benefits

• Maintenance saving

Shell Rimula R6 LM meets the long oil drain requirements of Mercedes-Benz, MAN, DAF and others, from the latest Euro 6 to older generation engines, to allow operators to optimize maintenance schedules and control maintenance costs.

• Emissions system compatibility

Advanced low-ash formulation helps control blocking of or poisoning of exhaust after-treatment devices, helping maintain vehicle emission compliance and engine fuel efficiency.

• Low wear, low deposits

Unique additive technology delivers high levels of piston cleanliness essential for long engine life and wear protection.

• Fuel economy

Shell Rimula R6 LM can save money in fuel consumption compared to high viscosity grades.

Main Applications



• On-highway heavy duty applications

Particularly suited for a wide range of trucking and transportation applications in modern low-emission vehicles from Mercedes-Benz, MAN, DAF, Volvo and others. Especially suitable for fleets with mixed Euro 2,3,4, 5 and 6 engine types.

• Low emission engine use

Shell Rimula R6 LM meets the latest requirements of most OEMs for Euro 4, 5, 6 engines and exceeds the performance requirements of industry specifications such as ACEA E6 and API CJ4.

• CNG engine oil performance

Shell Rimula R6 LM is approved for use in buses and trucks fitted with engines designed to run on 100% CNG such as those from Mercedes-Benz and MAN.

Specifications, Approvals & Recommendations

- ACEA E6, E9
- API CJ-4, CI-4, CH-4
- Caterpillar ECF-3
- Cummins CES 20081
- DAF Meets ACEA E6
- Deutz DQC IV-10 LA
- IVECO NG2 (Meets requirements)
- JASO DH-2
- MACK EO-O Premium Plus
- MAN M3477, M3271-1
- MB-Approval 228.51
- MTU Category 3.1
- Renault Trucks RLD-3
- Volvo VDS-4
- Scania Low Ash

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Typical Physical Characteristics

Properties			Method	Shell Rimula R6 LM 10W-40
Kinematic Viscosity	@40°C	mm ² /s	ASTM D445	96.8
Kinematic Viscosity	@100°C	mm ² /s	ASTM D445	14.5
Dynamic Viscosity	@-25°C	mPa s	ASTM D5293	6 080
Sulphated Ash		%	ASTM D874	0.95
Density	@15°C	kg/l	ASTM D4052	0.850
Flash Point (COC)		°C	ASTM D92	244
Pour Point		°C	ASTM D97	-36
Total base number (TBN)		mg KOH/g	ASTM D2896	12.9

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

Shell Rimula R6 LM oils are unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <http://www.epc.shell.com>

• Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Additional Information

• Advice

Advice on applications not covered here may be obtained from your Shell Representative.